Product Data

VIPER CDR VENT™



Complete Drained Roof

Description

CDR VENT™ is a 0.30-inch, randomly oriented, geometric patterned drainage and ventilation mat.

The product is designed to eliminate moisture and moisture vapor in cedar roofing, siding applications, and metal roofing applications.

CDR VENT is produced from an extruded polymer matrix of tangled monofilaments, which are heat-welded at the junctions to form a structure that spaces siding and roofing away from the inner sheathing.

The product is useful in cedar and metal roofing and siding applications in which a clean airspace is desired for ventilation and drainage.

Applications

- Roofing applications including cedar shingles and shakes
- Metal roofing applications
- ✓ Zinc roofing applications
- ✓ Siding applications
- ✓ Other roofing applications*

For Installation Instructions please see document: KC-02002

* For more information on roofing applications, please contact our office at 877-514-5336

Features and Benefits

Drainage of excess moisture and ventilation in one product

Lightweight and easy to handle

Simple installation with mechanical staple hammer

Polymer core resistant to most known corrosive chemicals, including solvents

Wide rolls for fewer seams

Core absorbs and releases no moisture

Provides no source for the promotion of MOLD, MILDEW or BACTERIA

Physical Properties

Description	Measurement			
Flame Spread	ASTM E84 Class A			
Core Polymer	Polymeric			
Thickness	0.30 in. 7.6 mm			
Weight of Core	9.9 oz/yd² (335.7 g/m²)			

Packaging

Document: KC-01002

Product Name	Product	Rolls	Units	Weight ր	per Roll	Length	per Roll	Coverage	e
	Part Number	per Unit	per Truck	lb	kg	ft	m	sq ft	sq m
VIPER CDR VENT	01-X-0006	18	26	14.0	6.3	50	15.2	200	18.6

LIMITED WARRANTY: Keene Building Products, Inc. warrants to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Keene Building Products, Inc. will correct any such failure by either replacing or repairing any defective goods, at Keene Building Products, Inc.'s option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The forgoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.



877 | 514 | 5336