

## HANDLING & STORAGE

Willki stone panels should be transported and stored in their original packaging until installation. Keep panels upright and avoid stacking heavy objects on top. Store in a dry, well-ventilated area away from direct moisture and sunlight.

## GENERAL CLEANING

During or after installation, dust from cutting or construction may accumulate. This can be easily removed using clean water and a soft nylon bristle brush.

For regular maintenance:

- Rinse the surface with water to remove dust and debris.
- For more stubborn dirt, use a mild detergent diluted in water and scrub gently with a soft brush.
- Rinse thoroughly to prevent soap residue from drying on the surface.

Do not use:

- Harsh chemicals or acids
- Metal-bristled brushes
- High-pressure washers
- Solvent-based cleaners

These may damage the surface, alter coloration, or compromise the integrity of the stone finish.

## OIL, GREASE & STAINS

For indoor applications such as kitchen backsplashes or BBQ areas, we recommend applying a breathable water-based sealant (e.g. Silane/Siloxane-based). These help resist grease and oil stains and can be reapplied every 3–5 years.

## DE-ICING PRODUCTS

Avoid the use of salt or de-icing chemicals near Willki stone panels. These products may cause surface deterioration over time, as with all concrete-based materials.

## INSPECTION & MAINTENANCE

We recommend periodically inspecting your installation for:

- Dirt or biological buildup
- Loose screws or anchor keys

Promptly clean or repair as needed to ensure long-term durability and aesthetic appeal.