



MODULAR REFRACTORY FIREPLACE

MAGNUM: 28" 36" 42" 48" 60" 72"

COMPLIES WITH APPLICABLE REQ. OF UL 127, ULC S610

WH-



- MADE IN USA
 MADE IN DENMARK

EARTHCORE INDUSTRIES, LLC.
JACKSONVILLE, FL 32256

CLEARANCE TO COMBUSTIBLES:

UNIT FRONT AND ISOKERN CHIMNEY

UNIT SIDES AND REAR

COMBUSTIBLE SHEATHING ABOVE OPENING TOP

SHEATHING OR TRIM TO OPENING SIDES

MANTLE ABOVE OPENING

OPENING TO SIDEWALL

HEARTH EXTENTION BEYOND FRONT

HEARTH EXTENTION BEYOND SIDES

COMBUSTIBLE FLOOR

INSULATION FROM FIREBOX

28", 36", 42", 48"

= 0 in.

= 1.5 in. (38mm)

= 8 in. (203mm)

= 8 in. (203mm)

= 14 in. (356mm)

= 26 in. (660mm)

= 20 in. (508mm)

= 12 in. (305mm)

= 4 in. (102mm)

= 3 in. (76mm)

60" & 72"

= 0 in.

= 1.5 in. (38 mm)

= 24 in. (610 mm)

= 9 in. (229 mm)

= 38 in. (965 mm)

= 48 in. (1219 mm)

= 33 in. (838 mm)

= 12 in. (305 mm)

= N/A N/A

= 3 in. (76 mm)

USE SOLID WOOD FUEL OR LISTED DECORATIVE GAS VENTED OR UNVENTED APPLIANCE. ALSO FOR USE WITH LISTED METAL CHIMNEY.
FIRE-LITE APPLICATION TO USE FTF13 OR EQUIVALENT CHIMNEY ONLY.

DO NOT USE A FIREPLACE INSERT OR OTHER PRODUCTS NOT SPECIFIED FOR USE WITH THIS PRODUCT. "WARNING" THIS FIREPLACE HAS NOT BEEN TESTED FOR USE WITH GLASS DOORS. TO REDUCE THE RISK OF FIRE OR INJURY, DO NOT INSTALL GLASS DOORS. IF DOORS ARE USED, OPERATE FIREPLACE WITH DOORS FULLY OPEN. WHEN BURNING A DECORATIVE GAS APPLIANCE IN THE FIREPLACE, LOCK THE DAMPER TO THE FULLY OPEN POSITION. ONLY UNVENTED GAS LOG SETS WHICH HAVE BEEN FOUND TO COMPLY WITH THE STANDARD FOR UNVENTED ROOM HEATERS, ANSI/IAS/AGA Z21.11.2, ARE TO BE INSTALLED IN THIS FIREPLACE. DO NOT OPERATE AN UNVENTED GAS LOG SET IN THIS FIREPLACE WITH THE CHIMNEY REMOVED.

SEE INSTALLATION AND OPERATING INSTRUCTIONS FOR THIS MODEL AND ICC # ESR-2316,
LA.RR # 25483, MEA #2490E.
ONLY UNVENTED GAS LOG SETS WHICH HAVE BEEN FOUND TO COMPLY WITH THE STANDARD FOR UNVENTED ROOM
HEATERS, ANSI/IAS/AGA Z21.11.2, ARE TO BE INSTALLED IN THIS FIREPLACE

CONTACT BUILDING OFFICIAL PRIOR TO INSTALLATION